

UNITED STATES PATENT APPLICATION

of

**Arthur W. WETZEL**

**John R. GILBERTSON, II**

**Jeffrey A. BECKSTEAD**

**Patricia A. FEINEIGLE**

**Christopher R. HAUSER**

and

**Frank A. PALMIERI, Jr.**

for

**A SYSTEM FOR CREATING MICROSCOPIC DIGITAL  
MONTAGE IMAGES**

## **A SYSTEM FOR CREATING MICROSCOPIC DIGITAL MONTAGE IMAGES**

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation-in-part of U.S. Patent Application No. 09/757,703, filed January 11, 2001, U.S. Patent Application No. 09/758,037, filed  
5 January 11, 2001, and U.S. Patent Application No. 09/788,666, filed February 21, 2001, all of which are currently pending and assigned to the assignee of the present invention.

### **FIELD OF THE INVENTION**

10 The present invention relates to microscopic digital imaging of complete tissue sections for medical and research use. In particular, it describes a method for high throughput montage imaging of microscope slides using a standard microscope, digital video cameras, and an illumination system.

### **BACKGROUND OF THE INVENTION**

15 Laboratories in many biomedical specialties, such as anatomic pathology, hematology, and microbiology, examine tissue under a microscope for the presence and the nature of disease. In recent years, these laboratories have shown a growing interest in microscopic digital imaging as an adjunct to direct visual examination. Digital imaging has a number of advantages including the ability to document disease, share findings, collaborate (as in telemedicine), and analyze morphologic findings by computer. Though  
20 numerous studies have shown that digital image quality is acceptable for most clinical and research use, some aspects of microscopic digital imaging are limited in application.

Perhaps the most important limitation to microscopic digital imaging is a "sub-sampling" problem encountered in all single frame images. The sub-sampling problem has two components: a field of view problem and a resolution-based problem. The field of view problem limits an investigator looking at a single frame because what lies outside  
25 the view of an image on a slide cannot be determined. The resolution-based problem occurs when the investigator looking at an image is limited to viewing a single resolution of the image. The investigator cannot "zoom in" for a closer examination or "zoom out"

for a bird's eye view when only a single resolution is available. Significantly, the field of view and resolution-based problems are inversely related. Thus, as one increases magnification to improve resolution, one decreases the field of view. For example, as a general rule, increasing magnification by a factor of two decreases the field of view by a factor of four.

To get around the limitations of single frame imaging, developers have looked at two general options. The first option takes the form of "dynamic-robotic" imaging, in which a video camera on the microscope transmits close to real time images to the investigator looking at a monitor, while the investigator operates the microscope by remote control. These systems have been used successfully in initial telepathology collaborations by allowing a distant consultant to view the specimen without the delays and losses associated with sending the physical slide to the consultant for review, and by allowing the consultant to view the entire slide, not just a few static images captured by the initial user.

However, these systems do not lend themselves to significant collaborations, documentation or computer based analysis. To be successful, remote transmission requires lossy video compression techniques to be used in order to meet the network bandwidth requirements, or requires significant delays in the image display if lossless transmission is used. In addition, lossy compression on the order required for real-time remote transmission, severely limits computer-based analysis, as well as human diagnosis, due to the artifacts associated with lossy compression techniques. Remote operation of a microscope also requires only a single user to use the instrument at one time, requiring instrument scheduling and local maintenance of the instrument and the slides to be viewed.

The second option being investigated to overcome the limitations inherent in single frame imaging is a montage (or "virtual slide") approach. In this method, a robotic microscope systematically scans the entire slide, taking an image at each "camera field" corresponding to the field of view of the camera. Camera field and field of view shall

hereinafter be referred to as the "field." The individual images are then "knitted" together in a software application to form a very large data set with very appealing properties. The robotic microscope can span the entire slide area at a resolution limited only by the power of the optical system and camera. Software exists to display this data set at any resolution on a computer screen, allowing the user to zoom in, zoom out, and pan around the data set as if using a physical microscope. The data set can be stored for documentation, shared over the Internet, or analyzed by computer programs.

The "virtual slide" option has some limitations, however. One of the limitations is file size. For an average tissue section, the data generated at 0.33  $\mu\text{m}/\text{pixel}$  can be between two and five gigabytes uncompressed. In an extreme case, the data generated from one slide can be up to thirty-six gigabytes.

A much more difficult limitation with the prior systems is an image capture time problem. Given an optical primary magnification of twenty and a two-third inch coupled device or "CCD", the system field of view is approximately  $(8.8 \text{ mm} \times 6.6 \text{ mm}) / 20 = 0.44 \times 0.33 \text{ mm}$ . A standard tissue section of approximately 2.25 square centimeters, therefore, requires approximately fifteen hundred fields to capture an image of the entire tissue section.

Field rate, which is the amount of time it takes to capture an image of a field and set-up the apparatus capturing the field for a following image capture, in montage systems is limited by three factors - camera frame rate (the number of camera images acquired per second), image processing speed (including any time required to read the camera data, perform any processing on the camera data prior to storage, and to store the final data), and rate of slide motion, which is the time required for the slide to be mechanically repositioned for the next image acquisition. Given today's technology, the rate of slide motion is a significant limiting factor largely because the existing imaging systems require the slide to come to a stop at the center of each field to capture a blur free image of the field.

For example, traditional bright field microscopic illumination systems were designed to support direct visual examination of a specimen on the field and therefore depend on a continuous light source for illumination. Continuous light, however, is a significant limitation for digital imaging in that the slide, which must move to capture an entire image, but must be stationary with respect to the camera during CCD integration, thus moving the slide from the light. Moreover, slide motion during integration results in a blurred image. Traditional montage systems, therefore, have had to move the slide (and stage) from field to field in a precise "move, stop, take image and move again" pattern. This pattern requires precise, expensive mechanics, and its speed is inherently limited by the inertia of the stage.

The three-dimensional characteristic of a typical tissue sample and the slide places additional limitations on the imaging system. Like all lenses, microscope optics have a finite depth of field – the distance within which objects will appear to be focused. A typical depth of field is about 8 microns for a 10× objective, and in general, as the magnification increases, the depth of field decreases. While microscope slides are polished glass, the flatness of the slide can vary on the order of 50 microns or more across the slide. The variations in the tissue sample thickness and any defects associated with placing the sample on the slide, such as folds in the tissue, also affect the optimal position of the slide with respect to the imaging optics. The magnitude of the optimal position and the limited depth of field of the microscope optics require the focus to be adjusted as the system moves from field to field. The time to refocus the system at each field also contributes to the overall capture time of the montage image.

Thus, a system is needed to reduce the image capture time. The system must also enable efficient and high quality imaging of a microscope slide via a high-resolution slide scanning process.

**SUMMARY OF THE INVENTION**

The present invention relates to a method and system for creating a high throughput montage image of microscope slides. The system includes an optical system, components that are used in a pre-scan processing, and components for auto-focusing by enabling accurate focus control of optical elements without requiring the stage to be stopped and refocused at each tile location. The optical system includes at least one camera, a motorized stage for moving a slide while an image of the slide is captured, a pulsed light illumination system that optically stops motion on the motorized stage while allowing continuous physical movement of the motorized stage, and a stage position detector that controls firing of the pulsed light illumination system at predetermined positions of the motorized stage. The components that are used in the pre-scan processing include an image-cropping component, a tissue finding component and a scan control component. The image-cropping component and tissue finding component identify tissue regions on the slide in the optical system and determine exact locations of tissue on the slide. The scan control component uses information about the locations to generate control parameters for the motorized stage and the camera. The components for auto-focusing include a focal point selection component, a focal surface determination component, and a scan component. The focal point selection component and the focal surface determination component use the control parameters to ensure that a high-quality montage image is captured. The scan component is able to capture a high-quality montage image by maintaining motion of the motorized stage and synchronization of the optical system. The scan component controls the stage position to maintain in-focus imaging during the scanning process without stopping the stage and refocusing at each location and fires a pulsed-illumination source at the appropriate position to guarantee image alignment between sequential camera images.

Accordingly, it is a benefit of the invention that it provides a microscopic imaging system for whole slide montage in which standard microscope optics, off the shelf cameras, a simple motorized stage, and a pulse light illumination system can be

used to produce precisely aligned image tiles, and acquire these image tiles at a speed limited primarily by the camera frame rate.

The present invention uses a strobe light, triggered by a direct Ronchi ruler or other stage-positioning device, to produce precisely aligned image tiles that can be made into a montage image of tissue sections on a microscope slide. Significantly, due to the short light pulse emitted by a strobe, clear images can be obtained without stopping the microscope stage. This significantly increases the image throughput while decreasing the expense and precision required in the stage mechanics.

In one embodiment, a strobe arc is placed at the position of the lamp bulb in a standard microscope system. The camera shutter is opened and the strobe is fired in response to the position of the stage as reported by a direct position sensor. If stray light is minimized, the camera exposure can be much longer than the strobe flash, allowing low cost cameras to be utilized.

It is another benefit of the invention to significantly increase the image throughput of a tiling image system by allowing, through the use of the strobe light, continuous motion of the slide under the microscope. The inventive system thus eliminates the need to stop the microscope stage to capture an image.

It is another benefit of the invention to reduce the demands of camera, stage, and strobe synchronization by controlling the firing of the strobe light based on direct stage position feedback, thereby substantially reducing the mechanical precision required of the stage and camera components.

It is another benefit of the invention to use a pre-scan process applied to a macroscopic image of the entire slide, to guide a high-resolution slide scanning process and ensure high-quality images of the entire specimen are acquired. The pre-scan process includes an image cropping component, a tissue finding component, a scan control component, a focus point selection component, a focal surface determination component, and a scan component. The image cropping and tissue finding components identify interesting regions on the slide to be scanned. The focus point selection and focal surface

determination components ensure that a high quality image is captured by the scanning process, by enabling accurate focus control to be maintained.

It is another benefit of the invention to use a high-resolution slide scanning process to control the operation of the motorized stage, camera and strobe illumination.

5 This process utilizes information gathered by the pre-scan process, namely the imaging regions and focus parameters, to control the positioning of the stage to image only the regions of interest and to ensure the individual images are well aligned and in focus.

Additional features and advantages of the invention will be apparent from the description that follows, or may be learned by practice of the invention. The objectives and advantages of the invention to be realized and attained by the microscopic image capture system will be pointed out in the written description and claims hereof as well as the appended drawings.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention that together with the description serve to explain the principles of the invention.

Fig. 1 is a partial isometric view of an embodiment of an imaging apparatus of the present invention;

Fig. 1a is a front view of the apparatus of Fig. 1;

Fig. 1b is a side view of the apparatus of Fig. 1;

Fig. 1c is a top view of the apparatus of Fig. 1;

Fig. 2 is a macroscopic image resulting from operation of an embodiment of the cropping component;

Fig. 3 illustrates a result of the tissue finding component;

Fig. 4 is an overlay of Figs. 2 and 3 illustrating the regions of the slide to be imaged;



Fig. 5 illustrates a result of the focus point selection component on a sample image;

Fig. 6 is a generated three-dimensional data set for the image of Fig. 5; and

Fig. 7 is a set of charts graphically depicting steps implemented in an embodiment of the inventive system.

### **DESCRIPTION OF THE PREFERRED EMOBODIMENTS**

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. The following paragraphs describe the functionality of the inventive system and method for focus controlled, high throughput montage imaging of microscope slides using a standard microscope, camera, and a motorized mechanical stage.

Fig. 1 illustrates a first embodiment of the imaging apparatus of the present invention. Figs. 1a-1c illustrate front, side, and top views, respectively, of the imaging apparatus illustrated in Fig. 1. It should be noted that not all components that may be included in an imaging apparatus are illustrated in Figs. 1-1c. For example, a stage support that attaches the stage to the imaging apparatus is not illustrated so as not to obstruct the view of other components. In this embodiment, a slide 112 to be imaged is placed on a thumbnail imaging position in a slide holder on a motorized stage 102. A single frame image containing the entire slide may be taken with a macro camera 106. One skilled in the art will recognize, however, that a suitable image may alternately be captured by combining multiple images taken by a microscopic camera such as microscopic camera 104. Microscopic and macroscopic images may furthermore be captured by use of two separate cameras or through the use of a single camera. The low-resolution image may be analyzed by software components, described below, to determine the locations of tissue on slide 112. This information can then be used to generate control parameters for stage 102 and microscopic camera 104 to ensure that the scanning process captures high quality images of only the tissue regions, substantially reducing the time to scan an average slide.

One skilled in the art will recognize that, although capturing the single macroscopic image saves time, it is not necessary for the operation of the invention. However, where a macroscopic image is to be used, multiple macroscopic images may be required to generate control parameters to the accuracy required based on the ratio of the macroscopic to microscopic magnifications and the camera specifications of each camera, if separate cameras are utilized.

Once the regions to be microscopically imaged are identified, the slide is scanned under the microscope optics. To facilitate rapid imaging of the slide and to avoid the stop image reposition delays associated with traditional imaging systems, a high-speed strobe light is used to optically stop the motion of the stage, thus the slide specimen, while allowing continuous stage motion. It should be apparent to one skilled in the art, that any pulsed illumination system may be used in place of the high-speed strobe light. To eliminate overlap or missed tissue between the microscope images, precise alignment of the stage and camera, along with accurate stage positioning, and camera and strobe synchronization, are required. To reduce the camera precision requirements, a direct stage position sensor is used to control the firing of the strobe, and thus the camera exposure.

In this fashion, the camera can be operated with a long exposure window in comparison to the very short strobe flash, allowing lower cost components, specifically the stage and camera, to be utilized.

Specifically in an embodiment illustrated in Figs. 1-1c, a pre-scan processing of the low-resolution or thumbnail image includes an image cropping component, a tissue finding component, a scan control component, a focus point selection component, and a focal surface determination component. Those pre-scanning components may then be followed by a scan component. The image cropping component and tissue finding component identify tissue regions on the slide to be scanned. The scan control component generates the necessary control parameters to scan only the regions of interest under the microscope optics. The focus point selection component and a focal surface

determination component ensure that the scan component captures a high-quality montage image, by enabling accurate focus control of the optical elements without requiring the stage to be stopped and refocused at each tile location, substantially reducing the acquisition time.

5 One step in processing the thumbnail image consists of flat-field correcting the macroscopic thumbnail image using a similar image that may have been obtained from the same camera and a blank slide. This removes any spatial light anomalies from the thumbnail image, which may reduce the efficiency of the tissue finding component. Depending upon the format, or size, of the camera and the aspect ratio of the slide, a  
10 portion of the image may contain non-slide objects such as a slide carrier (not shown in the figures). To remove these features, the thumbnail image may be cropped to remove non-slide objects, thus retaining only the slide information.

The image cropping may be accomplished via a two-pass process. The first pass in such a process determines an approximate location of the slide boundary, and the  
15 second pass fine-tunes this estimate. The search for the boundary is conducted over upper and lower intervals corresponding to the regions expected to contain the upper and lower slide edges, respectively. The slide or region of interest may be assumed to be positioned near the center, vertically, in the thumbnail image. The portion of the image falling outside of the identified slide boundary is removed. It should be noted that the  
20 cropping component and each of the other components described herein may operate on either a grayscale or color image. The image may also be cropped at the estimated edge locations, and then uniformly reduced in size to produce a small thumbnail image of the slide for rapid, visual slide identification.

Because the slide may not be oriented perfectly horizontally in the original  
25 thumbnail image, the identified slide edges are likely to lie at an angle. Thus, even after cropping, there may be remnants of the slide edges or cover slip in the cropped image. Therefore, the image cropping component attempts to identify pixel blocks that likely

contain these remaining edges and flags these blocks as edges that will not be considered for high resolution imaging by the tissue finding component.

The resulting cropped image generated by the image cropping component may serve as an input to the tissue finding component. This component locates regions in the thumbnail image that contain tissue of interest to a specialist. In order to minimize the time and storage space required to accomplish high-resolution slide imaging, the inventive system may capture only those regions of the slide that contain tissue. This approach may be facilitated by identifying regions containing tissue in the thumbnail image.

The tissue finding component identifies tissue regions via a sequence of filters that incorporate knowledge of the typical appearance and location of tissue and non-tissue slide regions. Initial filtering steps, in one embodiment, convert the image to a grayscale image and analyze the mean and standard deviation of the local pixel intensities. Pixel mean intensities may be used to differentiate tissue-containing regions from blank and other non-tissue regions, such as those containing the slide label or other markings. The standard deviation data may represent the amount of variation in pixel intensity values and thus is a good indicator of the border between tissue and the blank slide. The mean and standard deviation data is combined to generate a threshold value that is used to make an initial classification of tissue versus non-tissue. Subsequently, morphological filters may be applied to refine the classification based on the size and position of neighboring groups of potential tissue pixels.

The embodiment described above uses the mean and standard deviation of the local pixels as the basis for detecting regions of interest. One skilled in the art will recognize, however, that other image characteristics can also be used to identify the specimen from non-items of interest such as dust and scratches. That embodiment may also process a grayscale macroscopic image. It should be noted, however, that the pixel intensity differentiation tools described herein can be applied to each of the color components (traditionally, red, green and blue) of a color image in addition to being

applied to a grayscale image. Additional processing tools can also be applied between color components to refine the tissue finding accuracy and to remove features such as labels and writing that are not critical to the application, or to select user defined areas of interest to be scanned, such as regions circled by a purple marker.

5           The filters, which comprise the tissue finding component, process the pixels of the cropped grayscale thumbnail image in groups that correspond to slide regions, or tiles, that can be imaged individually during the high-resolution scanning process. These filters ensure that tiles only partially filled with tissue are classified as tissue-containing tiles. The final output of the filter sequence is a tiling matrix, the value of which  
10 indicates which tiles should be imaged. The tiling matrix subsequently guides the high-resolution scanning process.

          An example of the image cropping and tissue finding processes are shown in Figs. 2, 3 and 4. Fig. 2 illustrates the macroscopic image after flat-field correction and image cropping. Fig. 3 illustrates the results of the tissue finding component. The  
15 resulting tile matrix shown in Fig. 3 has a one-to-one correspondence to the field of view of the microscopic camera. White pixels (binary 1) signify fields to be captured and imaged, and black pixels represent regions not to image. Fig. 4 illustrates an overlay of Figs. 2 and 3 representing the sections of the slide to be imaged. For the application depicted in Figs. 2-4 (anatomical pathology), it is imperative to image all suspect regions  
20 that may contain tissue so conservative criteria are used in the tissue finding component, resulting in cover slip edges and writing etched into the slide to be identified as to be imaged. The savings in the acquisition time is represented by the ratio of the white to black areas of Fig. 3. For this image, only 53% of the slide region is to be imaged, including the label and cover slip edges, and etched writing on the slide.

25           At the completion of the tissue finding component, the scan control component interprets the tissue finding tile matrix (Fig. 3) and transposes the positions into actual stage coordinates for the microscopic imaging. A program running on a host computer controls the operation by communicating with a stage controller and microscopic camera

104. Actual scanning can occur in any fashion such as by rows or columns, or in a step fashion to image neighboring areas.

To achieve good focus for an entire slide, the surface that best represents the focal position of the sample with respect to the optical elements may be determined and used to automatically control the focus as the tissue is scanned under the microscope optics. These steps may furthermore be completed under the focus point selection component and the focus surface determination component.

In one embodiment, the focus point selection component evaluates the tissue regions of the thumbnail image and selects several points on which to initially focus the microscope optics. In this embodiment, that focus point selection is based on pixel intensity and distribution. Initially, tissue containing pixels or groups of tissue containing pixels are considered. Those pixels or pixel groups will be referred to hereinafter as regions. The regions that will be focussed upon, or focus regions, are then selected based on the relative contrast between the intensity of those regions within the thumbnail image and the distribution of those regions within the tissue containing portions of the image. It will be recognized that other intensity and/or distribution selection criterion may be utilized to select focus regions. After the focus regions are identified, a normalized focus surface such as a plane or curve may be drawn through the focus points and an equation, model, curve, or other method for describing appropriate focal lengths along that surface can be obtained. Proper focus for each region to be captured by the high-resolution scan may then be calculated by focusing on, for example, the plane or curved surface.

Selecting the appropriate focus region based on relative contrast improves the likelihood that regions that contain tissue will be selected over a method of picking focus regions based on a pre-selected grid-pattern. Selecting regions based on their overall distribution with respect to the tissue coverage area provides assurance that the resulting plane or surface will be representative of the entire slide and not limited to a small portion of the tissue, as could occur if selection were based solely on the relative contrast of pixels.

To select focus regions based on contrast, the present invention may select a number of focus regions having a desired contrast quality. For example, six to ten of the darkest regions may be selected from a back-lit image under the assumption that dark regions contain a large amount of tissue.

5           Distribution refers to the overall distribution of regions with respect to the tissue coverage area. Because a surface defined by the focus regions is the basis for maintaining the focus across the entire specimen during scanning, it is beneficial to have focus regions dispersed across the specimen rather than being grouped in close proximity to one another in one or more areas of the specimen. In that way, every point to be  
10 scanned will be close to a focus point. Thus, the scanned optical position at each point, as defined by the surface, should be very nearly the optimum in-focus position for that point.

          The focus point selection component may, for example, assure that at least one focus point is located within each of a number of pre-selected areas of the tissue. Those  
15 areas may, for example, be separate pieces of tissue on a slide. If a focus point does not exist on each pre-selected area, the focus point selection component may select additional regions, for example, having the desired contrast quality, until at least one focus point is identified on each pre-selected area. The number of data points required will depend on the actual three-dimensional structure defined by the specimen and slide, and the  
20 geometrical dimension of the surface to be fit. Once the surface has been determined, an error function can be calculated to determine the fit accuracy. For example, the mean square error of each selected focal region may be calculated to determine how much error exists between the surface fit and each focus region. If that error is greater than a predetermined acceptable error level, at one or more points, additional data points may be  
25 added to the calculation and/or points that have large errors may be eliminated and the surface may be recalculated under the assumption that the points having excessive errors were anomalies. A surface may then be fitted to those points to define a focal surface to be utilized when scanning the tissue.

In alternative embodiments, the focus points are either user definable through an input file or through a suitable user interface. In addition, for cases where the specimen locations are reproducible on the slides, the focus points can be predefined and repeated for each slide without the use of a macroscopic image or any preprocessing to find the tissue regions.

Once selected, each focus position is placed under the microscope optics in the focal surface determination component, and an auto-focus program determines the best-fit focus at each position. This generates a three-dimensional data set corresponding to the optimal specimen distance at each stage location. These data points are used as input to a surface fitting routine that generates the necessary control parameters for the slide scanning process.

At the completion of the focus point selection, the tissue information and the surface parameters are passed to the scan control component. This component is responsible for the motion of the stage and synchronization of the microscopic imaging system during montage image acquisition. To achieve accurate, well-aligned tiled images, the specimen must be positioned such that each camera image is aligned within the equivalent single pixel spacing in real or stage space (camera pixel size divided by the overall optical magnification). This usually entails a stage step of  $\delta x$  and  $\delta y$  where each step is directly related to the effective pixel size, which may be expressed in terms of camera pixel size / optical magnification, and the number of image pixels in the x and y directions respectively. For example, a 1300×1030 pixel, 10  $\mu\text{m}$  square pixel camera operated at 20× magnification results in  $\delta x = 10 \mu\text{m} * 1300 / 20 = 650 \mu\text{m}$  and  $\delta y = 10 \mu\text{m} * 1030 / 20 = 515 \mu\text{m}$ . To maintain focus during the scanning process, the stage must be positioned at the proper focal position as determined by the focus surface parameters:  $z_{ij} = f(x_i, y_j)$ , where  $z_{ij}$  is the vertical position of the slide with respect to the optical components,  $f(x_i, y_j)$  is the function used to represent the best focus surface, and  $x_i$  and  $y_j$  are the positions of each camera image in the x and y axes, respectively. The camera image positions can be expressed as linear relations between the starting position of the



stage ( $x_0$  and  $y_0$ ) and the step size associated with each image dimension:

$$x_i = x_0 + i * \delta x \text{ and } y_i = y_0 + i * \delta y.$$

Image montage scanning is traditionally accomplished by either scanning by rows or columns. Assuming that tiling is completed by scanning across a row in the x-

direction and stepping vertically in the y-direction after each row has been scanned, the stage is simply positioned at the appropriate position given by  $z_{i,j} = f(x_i, y_j)$ . Thereafter,

the stage is stopped and an image is acquired. If imaging is accomplished during continuous motion of the stage in the x-direction via a line scan camera or alternative imaging arrangement, the vertical velocity as a function of focal position  $x_i$  and time, can

be computed from the partial derivative of the focal surface:  $V_z(v_x, y_j) = \partial f(x_i, y_j) / \partial x * v_x$ , where  $V_z$  is the velocity of the vertical position of the stage and  $v_x$  is the velocity in the x-direction. The velocity of the vertical position of the stage can be used to control the optical position and maintain focus as images are acquired continuously across the row.

Fig 5. represents the results of the focus point selection component. This figure shows the thumbnail or macroscopic image of the region to be scanned. The light spots 504 overlaid on the specimen 506 represent the positions selected by the focus point selection component. These positions are placed under the microscope and auto-focused on each location. Fig. 6 illustrates the three-dimensional data set generated by focussing on each of the focus points of the specimen depicted in Fig. 5. For this slide, the best fit was planar,  $z(x,y) = dz/dx \ x + dz/dy \ y + z_0$ , where  $dz/dx$  ( $dz/dy$ ) is the slope or pitch of the plane with respect to x-axis (y-axis) and  $z_0$  is the vertical offset of the plane with respect to the z-axis. The best fit parameters for the specimen of Fig. 5 are also shown in Fig. 6.

At the completion of the pre-scan processing, the tile matrix and the stage control parameters are passed to a scanning-process control program. The scanning process control program controls the operation by communicating with a stage controller, a stage

position sensor, a camera and the strobe firing circuitry. In the invention, the computer program controls the operation of stage 102, camera 104 and strobe 108 illumination. The actual slide scanning can be automated to image entire slides, image only a portion of the slide or use a user-interface to allow the user to select the regions to be imaged.

5 Once a region has been selected for imaging, the program then controls the operation by communicating with a stage controller, a stage position sensor, camera 104 and strobe firing circuitry 108. Preferably, tiling is performed by moving stepwise along the short axis and with continuous motion along the long axis. In other words, tiling is done one row at a time. For this reason, a stage position is monitored and controlled differently  
10 along each stage axis. Along the short axis of the slide, the stage position is monitored and controlled, by the program, directly through the stage controller. Along the long axis, however, the stage position is monitored by a direct stage position sensor, which can be separate or part of the overall stage control circuitry.

15 In another embodiment, a Ronchi ruler attached to stage 102 is used for the stage position sensor. Those skilled in the art will recognize that any position sensor may be used in the invention. This sensor can be external to the stage controller or the positional information can be acquired directly from the stage controller with or without feedback.

20 For reference, a Ronchi ruler is a pattern of alternating light and dark bands, equally spaced along a substrate, typically either glass or plastic. A position sensor based on the Ronchi ruler utilizes a light sensor that is mechanically isolated from the ruler. As the ruler passes under the sensor, a series of electronic pulses is generated corresponding to the alternating light and dark bands of the ruler. These pulses can be used to monitor the position and direction of stage 102.

25 Based on the magnification of the optics and the camera utilized, strobe 108 is fired whenever the position sensor determines stage 102 has moved into the field of view of the next tile to be captured by the camera 104. The system continues to capture image tiles with precise alignment, until the images of all desired files have been captured or the

controlling program tells the system to stop. At the end of the capture process, the slide is removed and another slide can be inserted. With current technology, the rate-limiting step for image capture utilizing the present invention is the data transfer period in the camera.

Fig. 7 illustrates the signals of camera 104, stage 102, optical position detector, and strobe 108. Note that in Fig. 7, graphs 202 and 204 the signals from the optical position detector represent motion of stage 102, so their timing will vary depending on the speed of the stage movement. Where the system is triggered by the location of stage 102 as reported by the optical position sensor, precise movement of the stage movement is not necessary, allowing for the use of low cost stages 102.

The system can be run in a variety of modes, depending on how the camera is controlled. In one embodiment, the stage location, as sensed by a position sensor, fires both the camera 104 and the strobe 108 as indicated by the two traces at 204. In an alternate embodiment, camera 104 is free running and only strobe 108 is fired by stage position as indicated by a single trace at 204. This mode does not depend on uniform motion of stage 102 over the area imaged, because the strobe pulse is much shorter than the integration time of the camera 104, wherein the integration time is a time during which the camera is receiving an image. As long as the correct stage position is reached anytime within the integration time of camera 104, an excellent, well aligned image results.

Firing strobe 108 based on direct position information differs from the more traditional application of strobe photography. In traditional strobe photography, a strobe and camera are synchronized in time, and positional information regarding the objects being imaged can be inferred from the relative position within the image. When the present invention is operated in a mode wherein the position feedback controls both camera 104 and strobe 108, and camera 104 is not free running, each camera frame corresponds to an equally spaced positional change, independent of the stage velocity (speed and time variations in the speed). In the case that camera 104 is free running, the

stage speed has to be matched to the camera frame rate only to the accuracy such that the strobe pulse does not fall outside the exposure window. The relative time within the exposure window is irrelevant.

5 As will be understood by one skilled in the art, while the present invention describes a microscopic optical arrangement, the invention can also be applied to other optical imaging, inspection and illumination systems that are used for building up an image by matching the stage speed with the camera speed.

10 The foregoing description has been directed to specific embodiments of this invention. It will be apparent, however, that other variations and modifications may be made to the described embodiments, with the attainment of some or all of their advantages. Therefore, it is the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the invention.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197